




Specifications


Legs	STANDARD - 2" round post legs, 14 gauge steel. Welded insert for levelers/casters. Welded top plate of thickness 0.125" steel. Attachment requires (4-8) #12-14 screws. Levelers have 1/4 - 20 x 1-3/4" shank.
Leg Finish	Legs are finished with electrostatically applied powdercoat. Applied polyester powdercoat to be 2-3 mils in thickness and provide maximum chemical solvent and UV resistance. Scratch resistance to meet pencil hardness test of 2H or better. Standard Colors: (P) Platinum (B) Black
Work Surface	Manufactured using 1" thick, 45lb industrial particleboard. Standard is laminated with with HPL of 0.035" thickness with balanced backing sheet. All exposed edges are sealed. Glue line is a moisture and heat resistant PVA adhesive containing no VOC's. Metal inserts are inserted at factory.
Edgebanding	Machine applied using PUR adhesive (moisture-curing polyurethane, containing no VOC's 3mm PVC is standard.
Top Finishes	CFC Educational: Solids - Woodgrains - Nebulas - Patterns CFC Educational: Markerboard (upcharge to apply) Other Standard Finishes: Upcharge may apply
Heights Casters	(P) Primary: 24" (E) Elementary: 26" (D) Desk: 29" (S) Stool: 36" (B) Bar: 42" Standard: 2" (silver/black) hard plastic - double wheel Premium: 3" (gray) Soft Tread (constructed of high tech thermoplastic elastomer for extra traction)
	

Depths: 20", 24", 30", 36"
Widths: 32", 48", 60", 72"

RECTANGLE

Depths: 20", 24", 30", 36"
Widths: 32", 48", 60", 72"

RECTANGLE - Radius Corners




FLEX

36" x 36"
42" x 42"
48" x 48"


SQUARE

36" x 36"
42" x 42"
48" x 48"


SQUARE - Radius Corners




STARFISH




WAVE




WAVE END




HALF MOON




ROUND




HALF ROUND




AMOEBА



HORSESHOE
SMALL



HORSESHOE
LARGE



KIDNEY