




Specifications


Legs	ECONOMY - 2-3/8" round post legs, thick gauge aluminum. Replaceable plastic insert for levelers/casters. Separate top plate of thickness 0.125" steel. Attachment requires (4-8) #12-14 screws. Levelers, leg spacers and casters all screw into mounted plastic insert for easy adjustment.		
Leg Finish	Legs are finished with electrostatically applied powdercoat. Applied polyester powdercoat to be 2-3 mils in thickness and provide maximum chemical solvent and UV resistance. Scratch resistance to meet pencil hardness test of 2H or better. Standard Color: (P) Platinum Only		
Work Surface	Manufactured using 1" thick, 45lb industrial particleboard. Standard is laminated with with HPL of 0.035" thickness with balanced backing sheet. All exposed edges are sealed. Glue line is a moisture and heat resistant PVA adhesive containing no VOC's. Metal inserts are inserted at factory.		
Edgebanding	Machine applied using PUR adhesive (moisture-curing polyurethane, containing no VOC's. 3mm PVC is standard.		
Top Finishes	CFC Educational: Solids - Woodgrains - Nebulas - Patterns CFC Educational: Markerboard (upcharge to apply)		
Heights	(E) Elementary 26" (Levelers only)	(D) Desk 29"	(Levelers, Wheelbarrow, Casters)
Casters	Standard 3" (black) hard plastic—double wheel		

Depths: 20", 24", 30", 36"
Widths: 32", 48", 60", 72"


RECTANGLE

Depths: 20", 24", 30", 36"
Widths: 32", 48", 60", 72"


RECTANGLE - Radius Corners




FLEX




SQUARE




SQUARE - Radius Corners




STARFISH




WAVE




WAVE END




HALF MOON




ROUND




HALF ROUND




AMOEBA



HORSESHOE
SMALL



HORSESHOE
LARGE



KIDNEY