



Standard Sizes	Standard Heights
30 x 60	(D) Desk 30"
30 x 72	(S) Stool 36"
36 x 60	(B) Bar 42"
36 x 72	
42 x 60	
42 x 72	

## Specifications

<b>Base</b>	2" round, 14 gauge post legs with welded top plate. 4" round, 16 gauge post with 1/4" steel base plate. Base plate is attached to the post with bolts. Top mounting plate is welded to the post. Screws are used to attach top plates to worksurface
<b>Frame Finish</b>	Frame to be electrostatically applied powdercoat. All exposed metal parts to be prepared for coating with five stage wash that includes iron phosphate bath and acidic sealer for rust inhibitor. Applied polyester powdercoat to be 2-3 mils in thickness and provide maximum chemical, solvent, and UV resistance. Scratch resistance of finish to meet pencil hardness test of 2H or better. <b>Standard Finishes:</b> (B) Black (P) Platinum
<b>Work Surface</b>	Manufactured using 1" thick, 45 lb industrial particleboard. Standard HPL thickness of 0.035 thickness with balance backing sheet. All exposed edges are sealed. Glue line is a moisture and heat resistant PVA containing no VOC'S.
<b>Edgebanding</b>	Machine applied using PUR Adhesive (moisture-curing, polyurethane adhesive, containing no VOC's). 3mm PVC is standard.
<b>Top Colors</b>	<b>CFC Educational:</b> Woodgrains - Solids - Nebulas - Patterns - Other finishes (upcharge may apply)
<b>Available Options</b>	(G) Grommets (WM) Wire Management (E) Power/Data (per spec)