



662 Split Top with Wire Management

Available Sizes	
Depths	30"
Widths	60"
Heights	(D) Desk (S) Stool

Standard Top Configurations			
60"W		40	20
		30	30

*Custom widths require a minimum order

Specifications

Base	Fully unitized frame, wire welded. 16 gauge tubular construction with 1-1/4" square tubing, butt welded to form a solid rectangular support frame under top surface. Adjustable legs have 14 gauge 1-1/2" x 1-1/2" upper with 16 gauge 1-1/4" x 1-1/4" inserts. Set screws insert into weld tab for adjustment. Top is attached to frame using metal piano hinge. Top adjusts using metal bracket with multiple settings. Tilt tops over 30" include (2) metal brackets. Standard Finishes: (P) Platinum (B) Black (N) Natural Beige
Edgebanding	Machine applied using PUR Adhesive (moisture-curing, polyurethane adhesive, containing no VOC's).
Work Surface	Manufactured using 1" thick, 45 lb industrial particleboard. Standard is laminated with HPL of 0.035" thickness with a balanced backer sheet. All exposed edges are sealed. Glue line is a moisture and heat resistant PVA adhesive containing no VOC's.
Edge Options	(3) 3mm PVC
Top Colors	CFC Educational: Woodgrains - Solids - Nebulas - Other Standard Finish HPL (upcharge may apply)
Options	(L) Levelers (C) Casters (K) Keyboard Tray (M) Monitor Mount (H) Hanging CPU Holder (I) Instrument Catch (Black) (F) Standard 3mm PVC