



<b>Desk Height Frame</b>	<b>Leveler (20 - 32")</b>	<b>Caster (23 - 35")</b>
<b>Stool Height Frame</b>	<b>Leveler (28 - 38")</b>	<b>Caster (31 - 41")</b>
<b>Bar Height Frame</b>	<b>Leveler (33 - 43")</b>	<b>Caster (36 - 46")</b>

## Specifications

<b>Frame:</b>	Fully unitized frame, wire welded, 14 gauge tubular steel construction with 1-1/2" square tubing, butt welded to form a solid rectangular support frame under the top surface. Adjustable leg inserts can range from 20-46" and inserts are 1-1/4" 16 guage steel tubing. Screw type floor levelers.
<b>Frame Finish:</b>	Frame is finished with electrostatically applied powdercoat. All exposed metal parts to be prepared for coating with a five stage wash that includes iron phosphate bath and acidic sealer for rust inhibitor. Adjustable levelers, standard. Applied polyester powdercoat to be 2-3 mils in thickness and provide maximum chemical solvent, and UV resistance. Scratch resistance of finish to meet pencil hardness test of 2H or better. <b>Standard Colors</b> - Black, Platinum, Natural Beige
<b>Casters:</b>	3"Soft Tread constructed of high tech thermoplastic elastomer for extra traction on hard surface floors.
<b>Work Surface:</b>	Manufactured using 1" thick, 45lb. industrial particleboard. Standard is laminated with HPL of 0.035" thickness with a balanced backing sheet. All exposed edges are sealed. Glue line is a moisture and heat resistant PVA adhesive containing no VOC's.
<b>Edgebanding:</b>	Machine applied using a moisture-curing, polyurethane adhesive, containing no VOC's.

Visit [www.corilam.com](http://www.corilam.com) for more information or email us at [info@cfceducational.com](mailto:info@cfceducational.com)