

## Classroom Table - Clover Top Modules /Split Model 720-6200-S



### Specifications

<b>Case</b>	Constructed using either Glue-and-dowel or metal lock dowels with bolts. 3/4" 45 lb. particle board that is laminated with Thermofused melamine or HPL on both sides. Locking doors are standard. Base ships assembled and tops attach in field. Tray runners are clear. Trays sold separately. Units connect with hard plastic connectors, located underneath the tops.
<b>Tops</b>	Standard is 1" thick with specified HPL and banded with specified 3mm PVC.
<b>Base</b>	Replaceable base panel is 1" thick with through bolted 4" Soft Tread casters.
<b>Edgebanding</b>	Machine applied using PUR adhesive (moisture-curing, polyurethane, containing no VOC's).
<b>Work Surface</b>	Manufactured using 3/4" thick, 45 lb industrial particleboard core laminated to finish at 1-1/2". Standard is laminated with HPL of 0.035" thickness with a balanced backer sheet. All exposed edges are sealed. Glue line is a moisture and heat resistant PVA adhesive containing no VOC's.
<b>Standard Finishes</b>	<b>CFC Educational (720)</b> Woodgrains - Solids - Nebulas - Patterns <b>(723)</b> Any specified HPL <b>Marker Board Tops</b> - Upcharge to Apply