



Available Sizes	
Depths	24", 30", 36", 42"
Widths	72", 84", 96", 108", 120", 144"
Heights	(D) Desk (S) Stool (B) Bar



## Specifications

<b>Base Construction</b>	End panels and top are manufactured using 3/4" core laminated to finish at 1-1/2". Panels are then covered with specified HPL on both sides and edges are banded with specified finish. Self Edge HPL or 3mm PVC is standard based on availability. End panels have RF glued solid hardwood bottom with heavy duty inserts and levelers. Trough is manufactured using 3/4" core, laminated and banded to match. End panels, top and trough lock together using a glueless, barbed, hard plastic channel lock system. Flex grommets in top are standard. Plastic J-trough is standard for underneath cord management.
<b>Edgebanding</b>	Machine applied using PUR adhesive (moisture-curing, polyurethane, containing no VOC's).
<b>Work Surface</b>	Manufactured using 3/4" thick, 45 lb industrial particleboard core laminated to finish at 1-1/2". Standard is laminated with HPL of 0.035" thickness with a balanced backer sheet. All exposed edges are sealed. Glue line is a moisture and heat resistant PVA adhesive containing no VOC's.
<b>Standard Finishes</b>	<b>CFC Educational:</b> Woodgrains - Solids - Nebulas - Patterns - Other finishes (upcharge may apply)
<b>Options</b>	(E) Power - Based on requirements