



Specifications

Legs:

STANDARD - 2" round post legs, 14 gauge steel. Welded insert for levelers/casters. Welded top plate of thickness 0.125" steel. Attachment requires (4-8) #12-14 screws. Levelers have 1/4 - 20 x 1-3/4" shank.

Leg Finish:

Legs are finished with electrostatically applied powdercoat. Applied polyester powdercoat to be 2-3 mils in thickness and provide maximum chemical solvent and UV resistance. Scratch resistance to meet pencil hardness test of 2H or better.

Standard Colors: (P) Platinum (B) Black

Work Surface:

Manufactured using 1" thick, 45lb industrial particleboard. Standard is laminated with with HPL of 0.035" thickness with balanced backing sheet. All exposed edges are sealed. Glue line is a moisture and heat resistant PVA adhesive containing no VOC's. Metal inserts are inserted at factory.

Edgebanding:

Machine applied using PUR adhesive (moisture-curing polyurethane, containing no VOC's).

Top Finishes:

CFC Educational: Solids - Woodgrains - Nebulas - Patterns - Markerboard (upcharge applies)

Heights:

(P) Primary 24" (E) Elementary 26" (D) Desk 29" (S) Stool 36" (B) Bar 42"

Casters:

Standard: 2" (silver/black) hard plastic - double wheel

Premium: 2" (gray) Soft Tread (constructed of high tech thermoplastic elastomer for extra traction)



Visit www.corilam.com for more information or email us at info@cfceducational.com