



## Specifications

<b>Legs:</b>	<b>ECONOMY</b> - 2-3/8" round post legs, thick gauge aluminum. Replaceable plastic insert for levelers/casters. Separate top plate of thickness 0.125" steel. Attachment requires (4-8) #12-14 screws. Levelers, leg spacers and casters all screw into mounted plastic insert for easy adjustment.
<b>Leg Finish:</b>	Legs are finished with electrostatically applied powdercoat. Applied polyester powdercoat to be 2-3 mils in thickness and provide maximum chemical solvent and UV resistance. Scratch resistance to meet pencil hardness test of 2H or better. <b>Standard Color:</b> (P) Platinum
<b>Work Surface:</b>	Manufactured using 1" thick, 45lb industrial particleboard. Standard is laminated with with HPL of 0.035" thickness with balanced backing sheet. All exposed edges are sealed. Glue line is a moisture and heat resistant PVA adhesive containing no VOC's. Metal inserts are inserted at factory.
<b>Edgebanding:</b>	Machine applied using PUR adhesive (moisture-curing polyurethane, containing no VOC's).
<b>Top Finishes:</b>	CFC Educational: Solids - Woodgrains - Nebulas - Patterns - Markerboard (upcharge applies)
<b>Heights:</b>	(E) Elementary 26" (Levelers only) (D) Desk: 29" (Levelers, Wheelbarrow, Casters)
<b>Casters:</b>	<b>Standard: 3" (black) hard plastic—double wheel</b>

