



Model 530



Model 531



Model 532

## Specifications

### Post Finish:

Post to be black with electrostatically applied powdercoat. All exposed metal parts to be prepared for coating with a five stage wash that includes iron phosphate bath and acidic sealer for rust inhibitor. Applied polyester powdercoat to be 2-3 mils in thickness and provide maximum chemical, solvent, and UV resistance. Scratch resistance of finish to meet pencil hardness test of 2H or better.

**530:** Metal corner posts are 16 gauge tubular steel construction with 1-1/4" square tubing. Panels are connected with bolts.

### Worksurface:

Manufactured using 1" thick, 45lb. industrial grade particleboard core. Standard-Laminated with Wilsonart high pressure laminate of .035 thickness with a balanced backing sheet. All exposed edges are sealed. Glue line is moisture and heat resistant PVA containing no VOC's.

**531:** Laminated panels using 1" thick, 45 lb. industrial particleboard. Panels are connection with bolts. Black 3mm PVC is standard for panels. Matching 3mm is available.

**532:** Laminated panels using 3/4" thick, 45 lb. industrial particleboard. Adjustable metal legs. 22 3/4"- 29 3/4" in 1" increments

### Edgebanding:

Machine applied using a moisture-curing, polyurethane adhesive, containing no VOC's. 3mm PVC is standard on all panels. Matching tape is available.

### Standard Features:

Heavy duty structural fasteners, heavy duty adjustable floor levelers, upper shelf

### Options:

Pencil drawer, Keyboard tray, Keyboard tray with mouse, grommets where specified, wire management

Visit [www.corilam.com](http://www.corilam.com) for more information or email us at [info@cfceducational.com](mailto:info@cfceducational.com)